

The Pedofix® plates are anatomically shaped and can be applied far medioplantar with 3 or 4 fixed angle screws without jeopardizing the tendon of the M. tibialis. This technique can be combined with a cannulated cancellous screw (AD 3,5 mm) for dorsal compression of the arthrodesis.

Instruments and accessories

- 1301078

Pedofix implant and instrument set
- 1004045

Screwdriver handle silicone blue, cannulated
- 1001022

Driver TX 8-Lock / AO connector
- 1004042

Screwdriver handle silicone yellow, cannulated
- 1001008

Driver HEX 2,5 mm / AO connector cannulated
- 1001027

Driver HEX 2,5 mm / AO connector non-cannulated
- 1008038

Drill-guide with thread-fixation for 2,7 mm screws
- 1002527

Pincette
- 1006002

Depth-gauge
- 1203008

Head drill
- 1201054

Drill AD 2,0 mm cannulated / AO connector
- 1201053

Drill AD 2,0 mm cannulated / Stryker connector
- 1201038

Drill AD 2,5 mm cannulated / AO connector
- 1201037

Drill AD 2,5 mm cannulated / Stryker connector
- 1019105

Drill AD 2,5 mm cannulated / AO connector cannulated
- 1019104

Drill AD 2,5 mm cannulated / Round shaft
- 1001046

Position guide - plate holder / AO connector
- 1104009

K-wire tube
- 31-4111

K-wires L 140 mm, AD 1,1 mm

2,7 mm Pedofix® system components

- 

28-4109

Pedofix V2 titanium plate, size 1
- 

28-4110

Pedofix V2 titanium plate, size 2
- 

28-4114

Pedofix V2 titanium plate, size 2 long
- 


28-4028

MP1-Arthrodesis plate, 5-holes, L 28 mm
- 

28-4035

MP1-Arthrodesis plate, 6-holes, L 35 mm
- 


28-4045

MP1-Arthrodesis plate, 6-holes, L 45 mm
- 


28-3935

Reconstruction plate, 6-holes, L 35 mm
- 

28-3940

Reconstruction plate, 6-holes, L 40 mm
- 

28-4208 - 28-4228

Titanium screws
2,7 mm angular stable,
in 2 mm steps 8 mm - 28 mm
28-4208 - 28-4228
- 

28-4308 - 28-4328

Titanium screws 2,7 mm standard,
in 2 mm steps
8 mm - 28 mm
28-4308 - 28-4328
- 

SK 1335-20 - SK 1335-38

Cancellous screws 3,5 mm cannulated
for Lapidus arthrodesis,
in 2 mm steps 20 mm - 28 mm
SK 1335-20 - SK 1335-38

Supplementary

- 

Contour plates
Distal holes 2,7 mm screws
Proximal holes 3,5 mm screws
- 

Distal holes 2,7 mm screws
- 

Proximal holes 3,5 mm screws